




Integrated  
Photovoltaic  
Conference

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

**Alvaro de Gruijter**  
**Eurac Research**

# **Curtain Wall Façade Designs Integrated with PERC and Shingled HJT Technologies**



**Alvaro de Gruijter<sup>1</sup>, Diego Tamburrini<sup>2</sup>, Martina Pelle<sup>1</sup>, Martino Gubert<sup>2</sup>, Giuseppe de Michele<sup>2</sup>, Luis Fialho<sup>1</sup>, Laura Maturi<sup>1</sup>**

<sup>1</sup> Photovoltaic Energy Systems Group, Institute of Renewable Energies, Eurac Research, Bolzano, Italy

<sup>2</sup> Energy Efficient Buildings Group, Institute of Renewable Energies, Eurac Research, Bolzano, Italy

Contact: [alvarodegruijtereguiluz@eurac.edu](mailto:alvarodegruijtereguiluz@eurac.edu)

**eurac**  
research

Organised by

**etaflorence** \* **renewableenergies**



# FOURIER



# MC2.0



## Funded by the European Union

Project funded by



Schweizerische Eidgenossenschaft  
Confédération suisse  
Confederazione Svizzera  
Confederaziun svizra

Federal Department of Economic Affairs,  
Education and Research EAER  
State Secretariat for Education,  
Research and Innovation SERI


Swiss Confederation



*Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union. Neither the European Union nor the granting authority can be held responsible for them.*

Organised by

**eta**florence  **renewable**energies





# Presentation Overview


25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

## Introduction


Cell layers overview



PERC Cell



HJT Cell



### Introduction

### MC2.0 Curtain Wall Designs

### FOURIER Curtain Wall Designs

### Conclusions

**Building Integrated Photovoltaics**  
Insulated Glass Units  
PERC & HJT (Shingled) Cells

**Reliability**  
& Installation Process

**Performance**  
in a controlled environment

**Design findings**  
for next generation curtain wall  
BIPV systems

Organised by


etaflorence renewableenergies



# BIPV

## Building Integrated Photovoltaics


Replacing traditional building components, and fulfilling other functions required by the building envelope (such as weather protection, heat insulation and sunlight control)



To maximize the local use of the produced electricity (conceiving the buildings as micro energy hubs)



In harmony with the architectural language, and the overall image of the composition the context






# Where are we standing?

BIPV

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy



PV Distributed: Encompasses residential, commercial, industrial and off-grid projects




By 2030:  
**39%** of the total solar capacity!



# BIPV within Insulated Glass Units

## Curtain Wall Systems

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy



Sources:

[1] [Heli-On: Vetrata Isolante Fotovoltaica – Glass to Power](#),

[2] [Taurus Skylight - Photovoltaics Insulated Glass Unit \(PV IGU\) | Metsolar - Custom solar panels from EU manufacturer](#)

[3] [GruppoSTG – FOURIER Project RdS](#)

# Technologies of interest

Integrated within IGUs

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy


Cell layers overview



PERC Cell




HJT Cell



Technologies selected within IPV façade

# Manufacturing

## HJT Shingled Cells



Sources: [1] [Sonetto Shingling \(appliedmaterials.com\)](https://www.appliedmaterials.com), [2] [Shingled Technology All Black 420W 425W 430W Solar Panel For Home Manufacturer](#)

Organised by

etaflorence  renewableenergies 



Integrated  
Photovoltaic  
Conference

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

# MC2.0

## Curtain Wall Designs

1. Reliability of BIPV (PERC) integrated  
with Insulated Glass Units (IGU)






# MC2.0

## Curtain wall design from Glass To Power


25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy



Semifabricates



Insulated Glass Unit (IGU)  
Transparent Section











End Product


# Reliability of BIPV within IGUs

Performance: Damp Heat Tests

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

N. 1	Initial	500h DH	1000h DH
EL @ 100 % Isc			
IV Curve			
N. 2	Initial	500h DH	1000h DH
EL @ 100 % Isc			
IV Curve			

Maximum Power Degradation During Damp Heat Testing



## End Products (IGU + BIPV)

PV frame:

- Number of PV mini modules glued to an aluminum frame. Setup to be integrated between glasses for IGU

Integrated glass unit (IGU):


- Prototype of PV window
- PV frame mounted between two glass layers with Silicon.

# Reliability of BIPV within IGUs



Performance: Damp Heat, Thermal Cycling & Humidity Freeze Tests

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

IGU with BIPV integration




PV integrated in IGU Vs PV (no IGU)



IPV Samples Within IGU vs. IPV Samples Without IGU


- BIPV integration within an IGU does not negatively affect performance after thermal cycling tests (50TC)



# Installation Procedures

Building Integrated Photovoltaics

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy





Integrated  
Photovoltaic  
Conference

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

# FOURIER

## Curtain Wall Designs

2. Outdoor performance **in a controlled environment**






# Methodology

Controlled laboratory environment

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy



Test location: Eurac Research Outdoor Laboratories, Bolzano, Italy


Organised by

eta florence  renewable energies 

# Methodology

## Building Integrated Photovoltaics

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy



Façade design



Façade installation



Sensors installation

# Outdoor measurement campaign



25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

PR: 92%

PR: 88%

## IPV PERC MODULES

## IPV HJT (SHINGLING) MODULES



$$PR = \frac{Y_f}{Y_r} = \frac{\frac{E_{Out}}{P_0}}{\frac{H_i}{G_{STC}}}$$

Following IEC 61724: timesteps values discarded when irradiance POA < 100 W/m<sup>2</sup> and PR values > 1.

Outliers were also checked from the dataset based on the Interquartile Range (IQR) method:

$$IQR = Q3 - Q1$$


$$Lower\ Bound = Q1 - 1.5 * IQR$$

$$Upper\ Bound = Q3 + 1.5 * IQR$$

- P<sub>mpp</sub> (STC): 199.19 Wp
- 2 IPV PERC modules connected in series (large & small)

- P<sub>mpp</sub> (STC): 132.49 Wp
- 2 IPV HJT Shingling modules connected in series (large & small)


- Temperature gradients & the effect of PV are also important for the IGUs annealed glass!





# Conclusions

## BIPV Curtain Wall Façade Designs



### Reliability

- BIPV IGUs retained power > 97% after 1000 h DH & 50 TC
- TC tests showing BIPV integration within an IGU does not negatively affect performance

### Outdoor Performance

Integration with IGUs and Spandrel Façade systems achieved with:

- Grey coloured glass (**aesthetics**)
- IGU and spandrel systems (**technology**)
- PR ratios for facade cladding systems found at 92% (PERC) & 88% (HJT Shingled Cells) (**energy**)

Additional observations:

- Temperature gradients across layers and PV active and non-active areas require close monitoring to meet the facade requirements

Organised by

**eta**florence  **renewable**energies



25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

# Thank you!

This is an initiative of



Co-funded by  
the European Union

Grant N°101096126. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or CINEA. Neither the European Union nor the granting authority can be held responsible for them.

Project funded by



Schweizerische Eidgenossenschaft  
Confédération suisse  
Confederazione Svizzera  
Confederaziun svizra

Swiss Confederation

Federal Department of Economic Affairs,  
Education and Research EAER  
**State Secretariat for Education,  
Research and Innovation SERI**



# Reliability of BIPV within IGUs

## Appendix: Tests overview

25 – 26 November 2025  
Chamber of Commerce  
Florence, Italy

## Tests

### Thermal cycles (TC) in cycles:

- Temperature cycles between -40 °C and 85 °C following times given by IEC61215 (total time around 3-5 hours, typically **100** or 200 cycles)
- Compared to typical test: here no current injection.

### Damp heat (DH) in hours (h):

- 85 °C and 85 % relative humidity (RH) (typically for 500, **1000** or 2000 h)

### Humidity Freeze (HF) in cycles:

- 85 °C and 85 % RH for 20h → cycle to -40 °C (typically **10** or 50 cycles)
- Compared to typical test: here no current injection

### Characterization:

- IV curve (performance measurement using A+A+A+ flash tester)
- Visual image
- Electroluminescence (EL) image

## Samples

### End Products (IGU + BIPV)

#### PV frame:

- Number of PV mini modules glued to an aluminum frame. Setup to be integrated between glasses for IGU

#### Integrated glass unit (IGU):

- Prototype of PV window
- PV frame mounted between two glass layers with Silicon.